

# T11P

Visual Fault Locator (Pen type)



## Key Features

- Bright red laser at 650nm
- Pulsed and CW operation
- Outpower: 1mw,10mw,20mw
- 2.5mm universal connector
- 30 hours of operation(1mW)
- Pocket size design
- 1.25 mm adapter for LC (optional)

Support all type fiber connectors



ST



FC



SC




LC (optional)

## PRODUCT SPECIFICATION:

Model	T11P			
output power	1mW	10mW	20mW	30mW
Output wavelength	650nm			
Laser type	FP-LD			
2Hz	Yes			
Connector type	2.5mm universal for FC,SC,ST			
working temperature	-20~50°C			
Storage temperature	-20~50°C			
Battery	AA*2			
weight	80g			
Shape size	180*24mm			

## TESTING EFFECT:



## STANDARD PACKAGE:



## CONTACT US:

OrienTek Optical Technology Ltd.

## HEAD OFFICE:

Jianshan Industry Park, Liuhe District, Nanjing,  
Jiangsu, China

TEL: (+86) 25 8687 0598

FAX: (+86) 25 8687 0598

[www.orientekot.com](http://www.orientekot.com)

[sales@orientekot.com](mailto:sales@orientekot.com)

### Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in China.

In addition, the Export Administration Regulations (EAR) of the United States may be applicable.

In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of China or the Department of Commerce of the United States for details about procedures.